	SERIES	M2 SERIES MOTORIZED UNITS and ACCESSORIE	s FREQUE			IST	HYDRO	MOBILE	
AUTHORIZED DEALER NAME and ADDRESS:				USER/OWNER NAME and ADDRESS:					
NAM	1E of QUALI	FIED TECHNICIAN:	MOTORIZED UNIT MODEL	and SERIAL NUMBER:	DATE of INSPECTION:				
	Each Hydro Mobile motorized unit and its accessories must be submitted to a frequent inspection. Use the spaces below to monitor inspections that need to be performed every three months. Use the Notes and Comments form to indicate any discrepancy or any item found to be not acceptable. Any discrepancy must be reported and appropriate corrective action must be taken immediately. Corrective actions must be performed by a qualified technician. "Qualified" means a person who, by possession of a recognized degree, certificate or professional standing, or who by extensive knowledge, training and experience, has successfully demonstrated the ability to solve or resolve problems relating to the subject matter, the work or the project. Only a qualified person on the specific make and model of the Jydro Mobile equipment is allowed to perform maintenance inspections and repairs on Hydro Mobile units according to the guidelines, instructions, warnings and methods set out in the owner's manuals and Hydro Mobile training courses. All inspection steps included in the daily inspection checklist must be performed before the frequent inspection steps. It is recommended to use replacement parts manufactured by or recommended by Hydro Mobile. The use of substitution parts could not only void the warranty covering this motorized unit and its components but cause serious damages that could lead to injury or death. It is recommended to replenish and grease components only with fluids and lubricants recommended by Hydro Mobile.							Corrective ge, training model of the er's manuals d its	
		FOR EACH ENTRY VERIFIED. IF NECESSARY, TA	AKE CORRECTIVE ACTION BEFOR			ОК	CORRECTED	N/A	
	ESS and A legible cop	SAFETY y of the Owner's manual is present in the tool	box.	SERIAL	NUMBER (if applicable):				
BAS	F			CEDIAL	NUMBER (if applicable):				
		ion of base outriggers (4x) and outrigger shim	s.	SERIAL	NOMBER (II applicable):				
3	Check the ge	ometry of the base as per technical procedure	2.						
4	Inspect base	mast connection to make sure hardware is pr	esent, in good condition and secu	re. Replace mast bolt washers, if	required.				
5	Inspect base	outriggers for any welding defects, damaged	parts and excessive rust or corros	ion.					
6	Inspect base	structure for any welding defects, damaged p	arts or excessive rust or corrosion	I (LEFT).					
7 Inspect base structure for any welding defects, damaged parts or excessive rust or corrosion (RIGHT).									
8 Inspect center beam for any welding defects, damaged parts or excessive rust or corrosion.									
9 Inspect jack gears and mechanism (4x or 8x, as applicable). Grease jack mechanism, if necessary.									
MO [.]	TORIZED	UNIT STRUCTURE		SERIAL	NUMBER (if applicable):				
10 Check integrity of engine/motor access panel.									
11 Check integrity of mast tie door and hinges (LEFT).									
12 Check integrity of mast tie door and hinges (RIGHT).									
13	Check integri	ty of walkway access door, hinges and locking	g mechanism.						
14 Check motorized unit structure for any welding defects, damaged parts or excessive rust or corrosion, and any sign of distortion.					ion.				
ACC	ESS WA	LKWAY and COMPONENTS		SERIAL	NUMBER (if applicable):				
15 Check access walkway structure for any welding defects, damaged parts or excessive rust or corrosion.									
16 Check that safety straps are present and in good condition.									
GAS ENGINE / MOTOR SERIAL NUMBER (if applicable):					NUMBER (if applicable):			-	
		cal motorized unit, perform all the inspection asing of the motor bearings.	and maintenance operations on t	he motor as recommended by th	ne motor manufacturer,				
18	Perform reco	ommended maintenance on Honda engine as p	per instructions in Honda owner's	manual.					
POWER PACK and HYDRAULIC COMPONENTS SERIAL NUMBER (if applicable):									
19	Adjust engin	e RPM at full throttle and idle speed as per tec	chnical procedure.						
		Iraulic hoses and fittings for any leaks or signs	of wear.						
21 Check choke actuation.									
22 Check condition and adjustment of hydraulic control lever. Check condition of control lever rubber boot.									
								Page 1 of 3	

		M2 SERIES MOTORIZED UNITS and ACCESSORIE	FREQUENT INSPECTI	ON CHECKL	IST	HYDRO	MOBILE	
NAP	ME of QUALI	FIED TECHNICIAN:	MOTORIZED UNIT MODEL and SERIAL NUMBER:	DATE of INSPECTION:				
USE	CHECK MARK	ОК	CORRECTED	N/A				
-	OWER PACK and HYDRAULIC COMPONENTS SERIAL NUMBER (if applicable):							
	Check conditi							
24	Check conditi							
25	Check electric							
26	Check electric	al wiring and connections.						
27	Check engine	control rods.						
28	Check gasolin	e level. Replenish, if necessary.						
29	Check hydrau	lic oil level. Replenish, if necessary, with hydr	aulic oil recommended by Hydro Mobile.					
30	Check vibration	on insulator on power pack mounting.						
31	Clean battery	connections and perform battery load test a	s per technical procedure.					
32	Perform char	ging system test on Honda engine as per tech	nical procedure.					
LIF		CHANISM - LEFT	SERIAL	NUMBER (if applicable):				
33		raulic hoses and fittings for any leaks or signs						
34	Check conditi							
35	Check condition of each roller, roller pocket and shaft.							
36	5 Check cylinder hook, cam, locking mechanism and hardware. Make sure all is in good condition, functions properly and that hook engages correctly on mast rung.							
37	Check hydraulic cylinder for any leaks or damages.							
38	Check return mechanism of the secondary hook.							
39	Check rubber block under the cylinder hook. Replace if the rubber is worn.							
40	Check secondary hook, cam, locking mechanism and hardware. Make sure all is in good condition, functions properly and that hook engages correctly on mast rung.							
41								
42	2 Grease each roller using Prolab GS1000 only, as recommended by Hydro Mobile.							
43	Inspect each backup safety hook. Clean grease off the safety hook. Grease each backup safety hook using Prolab GS1000 only, as recommended by Hydro Mobile. Replace hook and pivot bolt if any sign of engagement is detected or suspected.							
LIF	IFTING MECHANISM - RIGHT Serial NUMBER (if applicable):							
44	Check all hyd	raulic hoses and fittings for any leaks or signs	of wear.					
45	Check conditi	on of cylinder guiding bar and springs.						
46	Check condition of each roller, roller pocket and shaft.							
47	Check cylinder hook, cam, locking mechanism and hardware. Make sure all is in good condition, functions properly and that hook engages correctly on mast rung.							
48	Check hydraulic cylinder for any leaks or damages.							
49	Check return							
50	Check rubber							
51	Check second on mast rung	Check secondary hook, cam, locking mechanism and hardware. Make sure all is in good condition, functions properly and that hook engages correctly on mast rung.						
52	Clean excess							
53	Grease each roller using Prolab GS1000 only, as recommended by Hydro Mobile.							
54	4 Inspect each backup safety hook. Clean grease off the safety hook. Grease each backup safety hook using Prolab GS1000 only, as recommended by Hydro Mobile. Replace hook and pivot bolt if any sign of engagement is detected or suspected.							
	,							
							D 2(2	

M2_	MAINTFR	EQ_1121
-----	---------	---------

	M2 SERIES MOTORIZED UNITS and ACCESSORIE	S FREQUENT INSPECT		ST	HYDRO	MOBILE	
NAI	ME of QUALIFIED TECHNICIAN:	MOTORIZED UNIT MODEL and SERIAL NUMBER:	DATE of INSPECTION:				
USE	CHECK MARK FOR EACH ENTRY VERIFIED. IF NECESSARY, T	AKE CORRECTIVE ACTION BEFORE INSERTING CHECK MARK.		ОК	CORRECTED	N/A	
GEI	NERAL	SERIA	NUMBER (if applicable):				
55	Check all stickers and make sure they are in place and legi sticker.	ate inspection validation					
56	Check outriggers, outrigger lock bolts and plank stop pins						
57	Inspect 84" (2,1 m) end guardrails (2x) for any welding def	ects, damaged parts or excessive rust or corrosion.					
58	Inspect 84" (2,1 m) guardrails (2x) for any welding defects condition.	, damaged parts or excessive rust or corrosion. Make sure gravit	lock is present and in good				
59	Inspect door guardrails (2x) for any welding defects, dama	ged parts or excessive rust or corrosion.					
60	Inspect movable / adjustable guardrails (2x if equipped) for	or any welding defects, damaged parts or excessive rust or corros	ion.				
61	Inspect plank-end guardrails for any welding defects, dam	aged parts or excessive rust or corrosion.					
W۲	IEN MOTORIZED UNIT IS IN USE	SERIAI	NUMBER (if applicable):				
62	Check integrity of wall tie brackets and anchor fasteners.						
63	3 Inspect guardrails for any welding defects, damaged parts and excessive rust or corrosion.						
64	64 Inspect mast sections for any welding defects, damaged parts and excessive rust or corrosion. Note serial numbers.						
65	65 Inspect mast tie components for any welding defects, damaged parts and excessive rust or corrosion.						
66	66 Perform all steps included in the daily/weekly inspection checklist.						
67	7 Perform all steps included in the frequent inspection checklist for a bridge.						
68	Perform all steps included in the frequent inspection chec						
TES	STS to RUN (as per technical procedu	res) Serial	NUMBER (if applicable):				
69	On an electrical motorized unit, test phase loss detector.						
70	On an electrical motorized unit, test phase synchronization	n					
71	Perform travel test and validate operating pressure as per	technical procedure.					
72	Test access walkway for proper operation and deploymen	t					
73	Test cylinder load holding capacity as per technical proced	lure.					
74	Test maximum admissible hydraulic operating pressure as	per technical procedure.					
	The undersigned certifies that this unit and its accessories have been properly inspected, in due time, that any discrepancy has been brought to the attention of the owner/user and that all discrepancies have been corrected prior to further use of this unit or its accessories.						

Name of QUALIFIED TECHNICIAN (IN PRINT)

	M2 SERIES MOTORIZED UNITS and ACCESSORIE							
NAME of QUALIFIED TECHNICIAN:		MOTORIZED UNIT MODEL and SERIAL NUMBER:		DATE of INSPECTION:		HYDRO MOBILE		
DATE ENTERED	NOTE or COMMENT		CORRECTIVE ACTION REQUIRED		DATE OF REPORT TO OWNER/USER	DATE OF COMPLETION FOR CORRECTIVE ACTION		
	_							
	_							
owner/user and	The undersigned certifies that this unit and its accessories have been properly inspected, in due time, that any discrepancy has been brought to the attention of the owner/user and that all discrepancies have been corrected prior to further use of this unit or its accessories.							
Signature of QI	JALIFIED TECHNICIAN	Name of QUA	LIFIED TECHNICIAN (IN PRINT)	DATE O	F INSPECTION			