| P SERIES - NARROW<br>MOTORIZED UNITS and ACCESSORIES   | s ANNUAL                              |                                 | N CHECKLIS                           | ST |                           |  |
|--|---------------------------------------|---------------------------------|--------------------------------------|----|---------------------------|--|
| AUTHORIZED DEALER NAME and ADDRESS:  | U                                     | SER/OWNER NAME and A            | ADDRESS:                             |    |                           |  |
|  |                                       |                                 |                                      |    |                           |  |
|  |                                       |                                 |                                      |    |                           |  |
|  |                                       |                                 |                                      |    |                           |  |
| NAME of QUALIFIED TECHNICIAN:  | MOTORIZED UNIT MODEL and              | SERIAL NUMBER:                  | DATE of INSPECTION:                  |    |                           |  |
|  |                                       |                                 |                                      |    |                           |  |
| Each Hydro Mobile motorized unit and its accessories must be submitted to an annual inspection. Use the spaces below to monitor inspections that need to be performed every year. Use the Notes and Comments form to indicate any discrepancy or any item found to be not acceptable. Any discrepancy must be reported and appropriate corrective action must be taken immediately. Corrective actions must be apprince, has successfully demonstrated the ability to solve or resolve problems relating to the subject matter, the work or the project. Only a qualified presson on the specific make and model of the Hydro Mobile equipment is allowed to perform maintenance inspections and repairs on Hydro Mobile units according to the guidelines, instructions, warnings and methods set out in the owner's manuals and Hydro Mobile tauting courses.<br>It is recommended to use replacement parts manufactured by or recommended by Hydro Mobile. The use of substitution parts could not only void the warranty covering this motorized unit and its components but cause serious damages that could lead to injury or death. It is recommended to replenish and grease components only with fluids and lubricants recommended by Hydro Mobile.   |                                       |                                 |                                      |    |                           |  |
| USE CHECK MARK FOR EACH ENTRY VERIFIED. IF NECESSARY, T  | AKE CORRECTIVE ACTION BEFORE IN       | SERTING CHECK MARK.             |                                      | ОК | CORRECTED N/A             |  |
| ACCESS and SAFETY Algorithm Algorith | hav                                   | SERIAL N                        | IUMBER (if applicable):              |    |                           |  |
| - ··· ·  | DOX.                                  |                                 |                                      |    |                           |  |
| BASE 2 Inspect base mast connection to make sure hardware is pri   | esent, in good condition and secure.  |                                 | IUMBER (if applicable):<br>required. |    |                           |  |
| 3 Inspect base outriggers (4x) and outrigger pivots.   |                                       |                                 |                                      |    |                           |  |
| <ul> <li>4 Inspect base outriggers for any welding defects, damaged p</li> </ul>   | narts and excessive rust or corrosion |                                 |                                      |    |                           |  |
| <ul> <li>5 Inspect base structure for any welding defects, damaged p</li> </ul>  |                                       |                                 |                                      |    |                           |  |
|  |                                       |                                 |                                      |    |                           |  |
|  | nisin, il necessary.                  |                                 |                                      |    |                           |  |
| MOTORIZED UNIT STRUCTURE 7 Check integrity of engine/motor access panel.   |                                       | SERIAL N                        | IUMBER (if applicable):              |    |                           |  |
| 8 Check integrity of mast tie door and hinges.   |                                       |                                 |                                      |    |                           |  |
| 9 Check motorized unit structure for any welding defects, da   | maged parts or excessive rust or cor  | rosion, and any sign of distort | ion.                                 |    |                           |  |
| GAS ENGINE / MOTOR   |                                       | SERIAL N                        | IUMBER (if applicable):              |    |                           |  |
| 10 On an electrical motorized unit, perform all the inspection including greasing of the motor bearings  | and maintenance operations on the r   | motor as recommended by th      | e motor manufacturer,                |    |                           |  |
| including greasing of the motor bearings.         11       Perform recommended maintenance on Honda engine as per instructions in Honda owner's manual.  |                                       |                                 |                                      |    |                           |  |
| POWER PACK and HYDRAULIC COMPON  | ENTS                                  | SERIAL N                        | IUMBER (if applicable):              |    |                           |  |
| 12 Adjust engine RPM at full throttle and idle speed as per teo  | hnical procedure.                     |                                 |                                      |    |                           |  |
| 13 Check all hydraulic hoses and fittings for any leaks or signs   | of wear.                              |                                 |                                      |    |                           |  |
| 14 Check choke actuation.  |                                       |                                 |                                      |    |                           |  |
| 15 Check control panel switches.   |                                       |                                 |                                      |    |                           |  |
| 16 Check electrical connection inside the control panels and b   | ioxes.                                |                                 |                                      |    |                           |  |
| 17 Check electrical wiring and connections.  |                                       |                                 |                                      |    |                           |  |
| 18 Check gasoline level. Replenish, if necessary.  |                                       |                                 |                                      |    |                           |  |
| 19 Check operation of control joystick. Check condition of joyst   | stick rubber boot.                    |                                 |                                      |    |                           |  |
| 20 Check vibration insulator on power pack mounting.   |                                       |                                 |                                      |    |                           |  |
| 21 Clean battery connections and perform battery load test as  | s per technical procedure.            |                                 |                                      |    |                           |  |
| 22 Inspect throttle cable and check adjustment.  |                                       |                                 |                                      |    |                           |  |
| 23 On a motorized unit equipped with a hydraulic cooler, test  | the fan and the sensor.               |                                 |                                      |    |                           |  |
| PN_MAINTANNUAL_1121<br>03 Nov 21   | R02                                   |                                 |                                      |    | Page 1 of 2<br>HM-FO-0909 |  |

|     | NW  | P SERIES - NARROW<br>MOTORIZED UNITS and ACCESSORII   | ANNUAL INSPECTIO   | N CHECKLIS                   |                   |
|-----|---|---|--|------------------------------|-------------------|
| NAN | ME of QUALI   | FIED TECHNICIAN:  | MOTORIZED UNIT MODEL and SERIAL NUMBER:  | DATE of INSPECTION:          |                   |
|     |   |   |  |                              |                   |
| USE | CHECK MARK  | FOR EACH ENTRY VERIFIED. IF NECESSARY,  | TAKE CORRECTIVE ACTION BEFORE INSERTING CHECK MARK.  |                              | OK CORRECTED N/A  |
| PO  | WER PAC   | K and HYDRAULIC COMPON  | IENTS SERIAL   | NUMBER (if applicable):      |                   |
| 24  | Perform char  | ging system test on Honda engine as per tec   | hnical procedure.  |                              |                   |
| 25  | Replace the h   | ydraulic return filter.   |  |                              |                   |
| 26  |   |   | ith hydraulic oil recommended by Hydro Mobile. Replenish with r<br>y two years with hydraulic oil recommended by Hydro Mobile. | ecommended hydraulic oil if  |                   |
| LIF | TING ME   |   | ,  | NUMBER (if applicable):      |                   |
| 27  | Check all hyd   | raulic hoses and fittings for any leaks or sign   | s of wear.   |                              |                   |
| 28  | Check conditi   | on of cylinder guiding bar and springs.   |  |                              |                   |
| 29  | Check conditi   | on of each roller, roller pocket and shaft.   |  |                              |                   |
| 30  | Check cylinde<br>mast rung.   | er hook, cam, locking mechanism and hardwa  | are. Make sure all is in good condition, functions properly and that   | t hook engages correctly on  |                   |
| 31  | Check hydrau  | lic cylinder for any leaks or damages.  |  |                              |                   |
| 32  | Check return  | mechanism of the secondary hook.  |  |                              |                   |
| 33  | Check rubber  | block under the cylinder hook. Replace if th  | e rubber is worn.  |                              |                   |
| 34  | Check second<br>on mast rung  |   | ware. Make sure all is in good condition, functions properly and the   | nat hook engages correctly   |                   |
| 35  | Clean excess  | grease off each roller.   |  |                              |                   |
| 36  | Grease each   | roller using Prolab GS1000 only, as recomme   | nded by Hydro Mobile.  |                              |                   |
| 37  |   | backup safety hook. Clean grease off the saf<br>e. Replace hook and pivot bolt if any sign of e | ety hook. Grease each backup safety hook using Prolab GS1000 or<br>engagement is detected or suspected.                        | nly, as recommended by       |                   |
| GEI | NERAL   |   | SERIAL   | NUMBER (if applicable):      |                   |
| 38  | Check all stick validation stick  | , , ,   | ible. Replace or update stickers as required. Update the appropria   | ate inspection               |                   |
| 39  | Check outrigg   | gers, outrigger lock bolts and plank stop pins  | for damages.   |                              |                   |
| 40  | Inspect 27" (6<br>models].  | 59 cm) guardrail (1x) with panel for any weld   | ing defects, damaged parts or excessive rust or corrosion [28" (71   | cm) guardrail on older unit  |                   |
| 41  | Inspect 27" (6  | 59 cm) guardrails (2x) for any welding defect   | s, damaged parts or excessive rust or corrosion [28" (71 cm) guard   | drail on older unit models]. |                   |
| 42  | Inspect 32" (8  | 31 cm) guardrails (2x) for any welding defect   | s, damaged parts or excessive rust or corrosion.   |                              |                   |
| 43  | Inspect 56" (1  | 193 cm) guardrail (1x) for any welding defect   | s, damaged parts or excessive rust or corrosion.   |                              |                   |
| 44  | Inspect 60" (1  | 1,5 m) guardrails (2x) for any welding defects  | , damaged parts or excessive rust or corrosion.  |                              |                   |
| 45  | Inspect plank   | -end guardrails for any welding defects, dam  | aged parts or excessive rust or corrosion.   |                              |                   |
| 46  | Inspect rear p  | platform extension for any welding defects, o   | lamaged parts or excessive rust or corrosion.  |                              |                   |
|     |   | N (as per technical procedu   |  | NUMBER (if applicable):      |                   |
| 47  |   | of emergency descent system as per technic  |  |                              |                   |
| 48  |   | el test and validate operating pressure as per  |  |                              |                   |
| 49  |   | load holding capacity as per technical proces   | jure.  |                              |                   |
| 50  |   | ncy stop button.  |  |                              |                   |
| 51  |   | eter circuit and bypass button.   |  |                              |                   |
| 52  | Test maximur  | m admissible hydraulic operating pressure as  | per technical procedure.   |                              |                   |
|     | The undersigned certifies that this unit and its accessories have been properly inspected, in due time, that any discrepancy has been brought to the attention of the owner/user and that all discrepancies have been corrected prior to further use of this unit or its accessories. |   |  |                              |                   |
| -   | nature of Q   | UALIFIED TECHNICIAN   | Name of QUALIFIED TECHNICIAN (IN PRINT)  | DATE OF INSPECTIC            | DN<br>Page 2 of 2 |

R02

| PIN |        | IA |
|-----|--------|----|
| 03  | Nov 21 |    |

| NW  | P SERIES - NARROW<br>MOTORIZED UNITS and ACCESSORIES |              |                            |  |                                 |   |  |
|---|--|--------------|----------------------------|--|---------------------------------|---|--|
| NAME of QUALIFIED TECHNICIAN:   |  | MOTORIZED UN |                            |  | SPECTION:                       | HYDRO MOBILE                                      |  |
|   |  |              |                            |  |                                 |   |  |
| DATE ENTERED  | NOTE or COMMENT                                      |              | CORRECTIVE ACTION REQUIRED |  | DATE OF REPORT<br>TO OWNER/USER | DATE OF<br>COMPLETION<br>FOR CORRECTIVE<br>ACTION |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
|   |  |              |                            |  |                                 |   |  |
| The undersigned certifies that this unit and its accessories have been properly inspected, in due time, that any discrepancy has been brought to the attention of the owner/user and that all discrepancies have been corrected prior to further use of this unit or its accessories. |  |              |                            |  |                                 |   |  |
| Signature of QUALIFIED TECHNICIAN     Name of QUALIFIED TECHNICIAN (IN PRINT)     DATE OF INSPECTION       PN_MAINTANNUAL_1121     DATE OF INSPECTION   |  |              |                            |  |                                 |   |  |